

Technical informations

Classico Series

Code	112-0000000001
Name	Welded locker 2 doors, 1 place
Dimensions (WxDxH)	615x500x1800 mm
Comp. Dim. (WxDxH)	613x480x1610 mm
N° doors	2
N° doors per column	1
Material	DC01/FeP01 UNI EN 10130
Weight (Kg)	33
Volume (m3)	0,55



general features

Base and body	Base on steel feet, 120 mm high with anti-oxidation plastic inserts, suitable for micrometric adjustable feet made of galvanized steel with plastic tip. Reinforcement ribs designed to accommodate the interlocking base. Body formed by single micro-joint paneling between roof and back to create slots for ventilation. Front thickness 30 mm, anti-cut edges folded three times.
Doors	Doors equipped with internal hinges with external 180 ° rotation angle, reinforcement on the hinges side and three times refolded anti-cut edges on the remaining sides, upper and lower ventilation slots, printed label holder.
Lock	Yale type cylinder lock with double key
Closing	One way lever
Internal construction	Double upper shelf h.247 mm.from the roof with hanger rod equipped with two "S" hooks in galvanized steel. Towel rail in chromed steel on the left, drip tray in plastic material on the right side.
Door color	Painting with epoxy powder color RAL 7035.
Body color	Painting with epoxy powder color RAL 7035.
Law	In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.

Configuration variants

Base	On base, on inox feet, without feet.
Door	Without ventilation, with holes type 1
Lock	padlock handle, embedded padlock, mechanic combination, electronic combination and coin lock (€1,00).
Closing	3-point closing lever.
Allestimento interno	Upper and lower shelf, without shelves.

Door color/ body



Technical informations

Code **112-00000000001**

Accessories

Sloping roof

Support bench

Mirror

Kit "S" hooks

Adjustable feet

Padlock

Anti-corrosion cover for feet

Spare parts

Cylinder lock type Yale with double key

Padlock handle

Door H. mm. 1605

Certifications

Check the list of certifications available in the appropriate section of the website or ask our commercial offices.

This technical sheet is exclusive property of Armet Srl.

Reproduction is forbidden within the law (art.171 Law 22/04/1941 ,n.633).

The fraudulent use, without proper written authorization, even partial and by whatever means, will be protected according to law.

The foregoing text contains information reserved to the intended recipient.

The content of this e-mail is confidential and its confidentiality is legally protected by DL196/03

